

07-07-00

A

IBM Docket No. RSW9-2000-0043-US1

In the United States Patent and Trademark Office

Patent Application Transmittal

Transmitted herewith for filing is the Patent Application of:

Inventors(s): Richard A. Floyd, John R. Hind, Marcia L. Peters, and Brad B. Topol

For: Apparatus and Method for Accessing Request Header Information Using a Transcoding Filter Servlet

JCS42 U.S. PTO
09/611158
07/06/00

Enclosed are

26 pages of specification, including 29 claims, plus 8 sheets of *formal* drawings.

X An assignment of the invention to International Business Machines Corporation, Armonk, New York 10504.

A certified copy of a/an application.

X Declaration and Power of Attorney.

X PTO-1449 & references

X A return post card

Other:

Filing Fee Calculation (For Other Than Small Entity)

Basic Fee:						\$690.00
Claims Fees:	Filed	Limit	Extra		Rate per Extra	
Total claims:	29	20	9		\$18.00	\$162.00
Independent claims:	3	3	0		\$78.00	\$0.00
Multiple Dependent Claim Presented					\$260.00	\$0.00
					Total	\$852.00

Please charge Deposit Account **09-0461** for the **Total** set forth above. The Commissioner is authorized to charge payment of any additional filing fees required under 37 CFR §1.16 and any patent application processing fees under 37 CFR §1.17 or to credit any overpayment to the identified account. A duplicate copy of this sheet is enclosed.

Express Mail Certificate

Express Mail Label No. EK956411752US

Date: July 6, 2000

I hereby certify that I am depositing the papers identified above with the U.S. Postal Service "Express Mail Post Office to Address" service on the above date, addressed to the Commissioner of Patents and Trademarks, Washington, DC 20231

Dianne Lane

BY:

Jeanine S. Ray-Yarletts

Attorney of Record Reg. No. 39,808

Date: July 6, 2000

IBM Corporation T81/062
Intellectual Property Law
PO Box 12195
Res. Tri. Park, NC 27709

Telephone: 919-543-2541 FAX 919-254-4330

Apparatus and Method for Accessing Request Header Information Using a Transcoding Filter Servlet

BACKGROUND OF THE INVENTION

1. Technical Field:

5 The present invention is directed to an apparatus and method for accessing request header information to use in transcoding response data.

2. Description of Related Art:

10 Transcoding is the process of customizing data content without requiring a change to the original generating application. Transcoding is performed for a variety of reasons including meeting the unique presentation requirements of a particular type of client device, a particular user, or a particular kind of
15 connection, implementing security policies, selectively hiding portions of the data that are not destined for a particular user, selectively encrypting the data, and the like. Transcoding is usually performed on a web server by a mechanism, e.g., a transcoding servlet or other
20 transcoding plugin, that acts as an intermediary between the client device and the content generator.

 When a client device sends a content request to a server, the request message includes a request header. The request header typically includes information

identifying the device type, user identification,
passwords, uniform resource locator (URL) requested,
HyperText Transfer Protocol (HTTP) method used (e.g., GET
or POST), and the like. This header data is passed by
5 the web server to the content generator process but is
not passed on to subsequent steps in the remaining output
path on the way to the requesting device, such as to the
transcoding mechanism.

This means that in the prior art, without changing
10 the content generator, that transcoding is limited to a
fixed manipulation which can not react to the client
device characteristics. The client is hence limited to
requesting content data from content sources that are
formatted for the particular type of client device. This
15 severely limits the content sources that some client
devices are able to have access to and the value that
transcoding can provide to the web server.

Figure 5 illustrates the prior art problem when a
browser on a small handheld personal computer (PC), with
20 a screen only capable of showing gray scale, makes a
request to a Java Servlet based web server. As shown in
Figure 5, the handheld PC sends an HTTP request message
from a Web browser 510 running on the handheld PC to a
Web server 520. The HTTP request is passed to a servlet
25 engine 530 which invokes a content generator servlet 540,
passing the request information. The retrieved content
is passed to a transcoding servlet 550 as generic HTML.

The transcoding servlet 550 transcodes the generic HTML and forwards it to the handheld PC via the servlet engine 530 and Web server 520, as a HTTP response message.

Thus, when the handheld PC targets a generic content
5 generator, for example a Java Server Page (JSP) authored for ideal presentation on a large desktop PC with a color display, the resulting web page presentation will be returned in a format not conducive for display on the device. This is because the transcoder has no way of
10 knowing the device characteristics which were in the original request header.

Thus, it would be advantageous to have an apparatus and method for providing client device characteristic information to a transcoding servlet in order to
15 customize data content for presentation on the client device.

SUMMARY OF THE INVENTION

The present invention provides an apparatus and method for accessing request header information used to transcode servlet output. The apparatus and method of the present invention includes a preamble that stores request header information from a request sent by a client device. The request header information is then provided to the transcoder along with the generated content data. The transcoder then performs appropriate transcoding on the generated content data based on the request header information supplied by the preamble. The transcoded content data is then sent to the client device. In this way, the client device is able to obtain content from a much larger set of content sources than with conventional systems.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an exemplary diagram of a distributed data processing system in which the present invention may be implemented;

Figure 2 is an exemplary diagram of a data processing system in which the present invention may be implemented;

Figures 3A and 3B are exemplary block diagrams illustrating exemplary embodiments of the present invention using servlet chain organizations;

Figure 3C is an exemplary block diagram illustrating an exemplary embodiment of the present invention wherein the preamble servlet and the transcoding servlet are embedded as extensions of the servlet engine;

Figure 3D is an exemplary block diagram illustrating an exemplary embodiment of the present invention in which a servlet chaining is not utilized and a controller is used in place of a targeted servlet;

Figure 4A is a flowchart outlining an exemplary operation of the preamble servlet of the present invention when processing a request for content from a client device;

5 **Figure 4B** is a flowchart outlining an exemplary operation of the transcoder of the present invention when processing a request for content from a client device; and

10 **Figure 5** is a block diagram illustrating a prior art mechanism for processing a content request from a client device.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference now to the figures, **Figure 1** depicts a pictorial representation of a distributed data processing system in which the present invention may be implemented. Distributed data processing system 100 is a network of computers in which the present invention may be implemented. Distributed data processing system 100 contains a network 102, which is the medium used to provide communications links between various devices and computers connected together within distributed data processing system 100. Network 102 may include permanent connections, such as wire or fiber optic cables, or temporary connections made through telephone connections.

In the depicted example, a server 104 is connected to network 102 along with storage unit 106. In addition, clients 108, 110, and 112 also are connected to network 102. These clients 108, 110, and 112 may be, for example, personal computers or network computers. For purposes of this application, a network computer is any computer, coupled to a network, which receives a program or other application from another computer coupled to the network. In the depicted example, server 104 provides data, such as boot files, operating system images, and applications to clients 108-112. Clients 108, 110, and 112 are clients to server 104.

Distributed data processing system 100 may include additional servers, clients, and other devices not shown. In the depicted example, distributed data processing system 100 is the Internet with network 102 representing a worldwide collection of networks and gateways that use the TCP/IP suite of protocols to communicate with one another.

At the heart of the Internet is a backbone of high-speed data communication lines between major nodes or host computers, consisting of thousands of commercial, government, educational and other computer systems that route data and messages. Of course, distributed data processing system 100 also may be implemented as a number of different types of networks, such as for example, an intranet, a local area network (LAN), or a wide area network (WAN). Figure 1 is intended as an example, and not as an architectural limitation for the present invention.

Referring to Figure 2, a block diagram of a data processing system that may be implemented as a server, such as server 104 in Figure 1, is depicted in accordance with a preferred embodiment of the present invention. Data processing system 200 may be a symmetric multiprocessor (SMP) system including a plurality of processors 202 and 204 connected to system bus 206. Alternatively, a single processor system may be employed. Also connected to system bus 206 is memory

controller/cache 208, which provides an interface to local memory 209. I/O bus bridge 210 is connected to system bus 206 and provides an interface to I/O bus 212. Memory controller/cache 208 and I/O bus bridge 210 may be integrated as depicted.

Peripheral component interconnect (PCI) bus bridge 214 connected to I/O bus 212 provides an interface to PCI local bus 216. A number of modems may be connected to PCI bus 216. Typical PCI bus implementations will support four PCI expansion slots or add-in connectors. Communications links to network computers 108-112 in Figure 1 may be provided through modem 218 and network adapter 220 connected to PCI local bus 216 through add-in boards.

Additional PCI bus bridges 222 and 224 provide interfaces for additional PCI buses 226 and 228, from which additional modems or network adapters may be supported. In this manner, data processing system 200 allows connections to multiple network computers. A memory-mapped graphics adapter 230 and hard disk 232 may also be connected to I/O bus 212 as depicted, either directly or indirectly.

Those of ordinary skill in the art will appreciate that the hardware depicted in Figure 2 may vary. For example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or

in place of the hardware depicted. The depicted example is not meant to imply architectural limitations with respect to the present invention. The data processing system depicted in Figure 2 may be, for example, an IBM
5 RISC/System 6000 system, a product of International Business Machines Corporation in Armonk, New York, running the Advanced Interactive Executive (AIX) operating system.

When a client device sends a content request to a
10 server, the content request includes a request header that includes identification information. This identification information identifies, for example, the type of client device, the capabilities of the client device, the URL of the requested web server resource, the
15 HTTP method being used, and additional HTTP headers. This information is stored by the preamble in accordance with the present invention, in a manner to be described in more detail hereafter, for use during transcoding of generated content data so that the content data is
20 properly formatted for the client device. Once the content data is generated by the server, the content data and the request header information are used for transcoding and the transcoded data is sent to the client device. In this way, general content data may be
25 customized for the particular client device requesting the content data.

The server 200 executes one or more servlets for

performing various types of processing of client requests. A servlet is an application that runs in a web server or application server and provides server-side processing, typically to access a database or perform
5 e-commerce processing.

One such servlet that is executed by the server 200 is a transcoding filter servlet. The transcoding filter servlet performs transcoding of content data from one format to another such that the content data is in a form
10 that is customized for the particular client device from which the content request was received. The transcoding filter servlet may be, for example, a Multipurpose Internet Mail Extensions (MIME) filter servlet. MIME encodes the files using one of a number of encoding
15 methods and decodes it back to its original format at the receiving end. A MIME header is added to the file which includes the type of data contained and the encoding method used. S/MIME (Secure MIME) is a version of MIME that adds RSA encryption for secure transmission and may
20 also be used without departing from the spirit and scope of the present invention.

In addition to the transcoding filter servlet, the server 200 of the present invention also executes a preamble servlet. The preamble servlet performs the
25 function of receiving a content request message from a client device, storing the request header information included in the content request message, and providing

the request header information to the transcoding filter
servlet when the content data is sent to the transcoding
filter servlet. The transcoding filter servlet may then
make use of the request header information to determine
5 how to transcode the content data for use by the client
device.

Those of ordinary skill in the art will recognize
that there may be several methods for storing and
retrieving header information in accordance with the
10 present invention. For example, one possible embodiment,
which may be executed on IBM WebSphere 2.0.3 may store
and retrieve header information in the following manner.

In the following embodiment, header values are
aggregated and concatenated into a Java String object. A
15 reference to the String object may be stored as an
attribute of the Servlet engine's session object using,
for example, the following Java code section:

```
com.sun.server.http.HttpServiceRequest bradReq =  
    (com.sun.server.http.HttpServiceRequest) req;  
20 bradReq.setAttribute("brad", headerValues);
```

This stored header information can then be retrieved
by a MIME filter transcoding servlet using the following
code section:

```
com.sun.server.http.HttpServiceRequest bradReq =  
25 (com.sun.server.http.HttpServiceRequest) req;  
String headerValues =(String)  
bradReq.getAttribute("brad");
```

The transcoding filter servlet and the preamble servlet

may be organized in a chain with regard to one another. Servlet chaining is generally known in the art and thus, the details of implementing the chaining are not set forth here. See, for example, Hunter, J, Crawford, W.,
5 Java Servlet Programming, O'Reilly and Associates, 1998.

Figures 3A and 3B provide exemplary block diagrams illustrating exemplary embodiments of the present invention in which servlet chaining is utilized. Figures 3A and 3B are directed to the execution order for sending
10 the requested content data back to a client device, however, similar chaining is applicable to the receipt of the content request from the client device.

As shown in Figure 3A, a first embodiment of the present invention includes a preamble servlet 340, a
15 content generator 350 and a transcoding servlet 360. The preamble servlet 320 stores request header information obtained from the request message sent by the client device 310. This request header information is stored in a data structure identified with a particular request.
20 In this way, when a response message is generated with the requested content data, the response message may be matched to the request message and thus, the request header information may be retrieved from the data structure in the preamble servlet 340.

25 The preamble servlet 340 passes the request header information to the transcoding servlet 360. In addition,

the preamble servlet 340 echoes the request message to the content generator 350 so that the requested content data can be generated and forwarded to the transcoding servlet 360.

5 The transcoding servlet 360 performs appropriate transcoding of the content data based on the client device information, e.g., client device characteristics, obtained from the request header information. Such transcoding is generally known in the art and thus, the
10 details of the transcoding operation will not be described here. See, for example, A. Fox, S. Gribble, Y. Chawathe, E. Brewer, "Adapting to Network and Client Variation Using Infrastructural Proxies: Lessons and Perspectives", *IEEE Personal Communications*, vol. 5, no.
15 4, Aug. 1998, pp. 10-19. The transcoded content data is then sent to the client device 310 in the appropriate format for presentation by the client device 310.

 Figure 3B provides an alternative servlet chain that may be utilized with the present invention. The
20 embodiment depicted in Figure 3B differs from that of Figure 3A in that the request message from the client device 310 is passed to both the preamble servlet 340 and the content generator 350 directly from the servlet engine 330. In this way, the preamble servlet may
25 extract the header information from the request message and store it while the content generator 350 is

generating the requested content. Throughput may thereby be increased.

Figure 3C is an exemplary block diagram that illustrates an additional alternative embodiment of the present invention. The embodiment shown in **Figure 3C** operates in a similar manner as the embodiment shown in **Figure 3A**, and optionally as the embodiment shown in **Figure 3B** (indicated by the dashed line extending to the content generator). The difference between the embodiments shown in **Figure 3A-3B** and the embodiment in **Figure 3C** is that the preamble servlet 340 and the transcoding servlet 360 are extensions of the servlet engine 330 rather than separate servlets.

Figure 3D illustrates still another embodiment of the present invention in which servlet chaining is not utilized. As shown in **Figure 3C**, a controller 370 is utilized in place of a targeted servlet. The controller 370 invokes the preamble servlet 340 functions and transcoding servlet 360 functions and makes calls to the content generator 350 for the requested content. The preamble servlet 340 functions and the transcoding servlet 360 functions may be implemented using, for example, corresponding Java methods, subroutines, and other types of computer implemented code.

As mentioned above, in conventional systems, the request header information is not available to the

transcoding process. Thus, the client device is limited to only a particular subset of content sources from which the client can obtain content data. With the present invention, however, the client device is able to obtain
5 content data from any content source that is capable of transcoding the content data to a format useable by the client device. This is made possible because the transcoding process, e.g., the transcoding filter servlet, is allowed access to the request header
10 information to ascertain the proper transcoding for the client device.

Figure 4A is a flowchart outlining an exemplary operation of the preamble servlet of the present invention when processing a content request from a client
15 device. As shown in **Figure 4A**, the operation starts with the receipt of a request from the client device (step 410). This request includes a request header as described above. The client device characteristic information from the request header is stored in a data
20 structure (step 420) and the request message is echoed to the content generator (step 430). As described above, the storage of the client device characteristic information may be done using a data structure indexed in such a manner that the client device characteristic
25 information may be retrieved when generating a response message.

Figure 4B is a flowchart outlining an exemplary

operation of the transcoding servlet of the present invention when processing a content request from a client device. As shown in Figure 4B, the operation starts with the requested content data being received by the

5 transcoding servlet (step 440). The client device characteristic information is retrieved from the preamble servlet (step 450) and used to transcode the requested content data (step 460). The transcoded content data is then sent to the client device in a format suited for

10 presentation by the client device (step 470).

Thus, the present invention provides a mechanism by which the characteristic information of a client device may be known to a transcoding servlet so that proper formatting of requested content data may be performed.

15 With the present invention, network servers may store generic content data for a plurality of different client devices, which can be customized by a transcoding process so that the content data is properly presented on the particular client device that requested the content data.

20 It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in

25 the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of

signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and

5 transmission-type media, such as digital and analog communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded
10 formats that are decoded for actual use in a particular data processing system.

The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the
15 invention in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of
20 ordinary skill in the art to understand the invention for various embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS:

What is claimed is:

1 1. A method of formatting content data for presentation
2 on a client device, comprising:
3 receiving a request for the content data, the
4 request having client device characteristic information;
5 storing the client device characteristic
6 information;
7 generating the content data; and
8 transcoding the content data using the client device
9 characteristic information to produce transcoded content
10 data.

1 2. The method of claim 1, wherein the step of storing
2 the client device characteristic information is performed
3 in a preamble servlet.

1 3. The method of claim 2, wherein the step of
2 transcoding is performed by a transcoding servlet, and
3 wherein the transcoding servlet obtains the client device
4 characteristic information from the preamble servlet.

1 4. The method of claim 1, wherein the content data is
2 generic content data, and wherein the transcoded content
3 data is content data that is formatted for presentation

4 on the client device.

1 5. The method of claim 1, wherein storing the client
2 device characteristic information includes storing the
3 client device characteristic information in a data
4 structure indexed for retrieval when generating a
5 response message.

1 6. The method of claim 1, further comprising:
2 generating a response message including the
3 transcoded content data; and
4 transmitting the response message to the client
5 device.

1 7. The method of claim 1, wherein the request is an
2 hypertext transport protocol request message, and wherein
3 the client device characteristic information is obtained
4 from a header of the hypertext transport protocol request
5 message.

1 8. The method of claim 1, wherein the step of storing
2 the client device characteristic information and the step
3 of generating the content data are performed at
4 approximately a same time.

1 9. The method of claim 7, wherein the header includes
2 at least the client device type and one or more of user

3 identification, passwords, uniform resource locator (URL)
4 requested and HyperText Transfer Protocol (HTTP) method
5 used.

1 10. The method of claim 1, wherein the method is
2 implemented in a network server.

1 11. An apparatus for formatting content data for
2 presentation on a client device, comprising:
3 a preamble servlet;
4 a content generator coupled to the preamble servlet;
5 and
6 a transcoding servlet coupled to the content
7 generator, wherein when a request for the content data is
8 received by the apparatus, the request having client
9 device characteristic information, the preamble servlet
10 stores the client device characteristic information in a
11 data structure and the content generator generates the
12 content data, and wherein the transcoding servlet
13 transcodes the content data using the client device
14 characteristic information to produce transcoded content
15 data.

1 12. The apparatus of claim 11, wherein the transcoding
2 servlet obtains the client device characteristic
3 information from the preamble servlet.

1 13. The apparatus of claim 11, wherein the content data
2 is generic content data, and wherein the transcoded
3 content data is content data that is formatted for
4 presentation on the client device.

1 14. The apparatus of claim 11, wherein the preamble
2 servlet stores the client device characteristic
3 information in a data structure indexed for retrieval
4 when generating a response message.

1 15. The apparatus of claim 11, further comprising a
2 servlet engine that generates a response message
3 including the transcoded content data and transmits the
4 response message to the client device.

1 16. The apparatus of claim 11, wherein the request is an
2 hypertext transport protocol request message, and wherein
3 the client device characteristic information is obtained
4 from a header of the hypertext transport protocol request
5 message.

1 17. The apparatus of claim 11, wherein the preamble
2 servlet stores the client device characteristic
3 information and the content generator generates the
4 content data at approximately a same time.

1 18. The apparatus of claim 16, wherein the header

2 includes at least the client device type and one or more
3 of user identification, passwords, uniform resource
4 locator (URL) requested and HyperText Transfer Protocol
5 (HTTP) method used.

1 19. The apparatus of claim 11, wherein the preamble
2 servlet echoes the request to the content generator.

1 20. The apparatus of claim 11, wherein the preamble
2 servlet, content generator and transcoding servlet are
3 implemented in a network server.

1 21. A computer program product in a computer readable
2 medium for formatting content data for presentation on a
3 client device, comprising:
4 first instructions for receiving a request for the
5 content data, the request having client device
6 characteristic information;
7 second instructions for storing the client device
8 characteristic information;
9 third instructions for generating the content data;
10 and
11 fourth instructions for transcoding the content data
12 using the client device characteristic information to
13 produce transcoded content data.

1 22. The computer program product of claim 21, wherein

2 the second instructions are implemented in a preamble
3 servlet.

1 23. The computer program product of claim 22, wherein
2 the fourth instructions are performed by a transcoding
3 servlet, and wherein the transcoding servlet obtains the
4 client device characteristic information from the
5 preamble servlet.

1 24. The computer program product of claim 21, wherein
2 the content data is generic content data, and wherein the
3 transcoded content data is content data that is formatted
4 for presentation on the client device.

1 25. The computer program product of claim 21, wherein
2 the second instructions include instructions for storing
3 the client device characteristic information in a data
4 structure indexed for retrieval when generating a
5 response message.

1 26. The computer program product of claim 21, further
2 comprising:
3 fifth instructions for generating a response message
4 including the transcoded content data; and
5 sixth instructions for transmitting the response
6 message to the client device.

1 27. The computer program product of claim 21, wherein
2 the request is an hypertext transport protocol request
3 message, and wherein the client device characteristic
4 information is obtained from a header of the hypertext
5 transport protocol request message.

1 28. The computer program product of claim 21, wherein
2 the first instructions and third instructions are
3 performed at approximately a same time.

1 29. The computer program product of claim 22, further
2 comprising fifth instructions for echoing the request
3 from the preamble servlet to a content generator.


ABSTRACT OF THE DISCLOSURE

Apparatus and Method for Accessing Request Header Information Using a Transcoding Filter Servlet

The present invention provides an apparatus and
5 method for accessing request header information used to
transcode servlet output. The apparatus and method of
the present invention includes a preamble that stores
request header information from a request sent by a
client device. The request header information is then
10 provided to the transcoder along with the generated
content data. The transcoder then performs appropriate
transcoding on the generated content data based on the
request header information supplied by the preamble. The
transcoded content data is then sent to the client
15 device. In this way, the client device is able to obtain
content from a much larger set of content sources than
with conventional systems.

Figure 1

RSW9-2000-0043-US1






Figure 2

RSW9-2000-0043-US1




Figure 3A

RSW9-2000-0043-US1




Figure 3B

RSW9-2000-0043-US1




Figure 3C

RSW9-2000-0043-US1




Figure 3D

RSW9-2000-0043-US1

Figure 4A

RSW9-2000-0043-US1





Figure 4B

RSW9-2000-0043-US1






Figure 5

RSW9-2000-0043-US1

**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**Apparatus and Method for Accessing Request Header Information Using a
Transcoding Filter Servlet**

the specification of which is identified by the attorney (IBM) Docket Number appearing above.

I hereby state that I have reviewed and understand the contents of the above- identified specification, including the claims.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

<u>Number</u>	<u>Country</u>	<u>Day/Month/Year</u>	<u>Priority Claimed</u>
---------------	----------------	-----------------------	-------------------------

I hereby claim the benefit (a) under Title 35, United States Code, §119(e) of any U.S. application listed below and identified as a provisional application or (b) under Title 35, United States Code, §120 of any U.S. application listed below and not identified as a provisional application, and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior U.S. application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information material to the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application

Prior U.S. Applications

<u>Serial No.</u>	<u>Filing Date</u>	<u>Status</u>
-------------------	--------------------	---------------

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Bruce A. Clay, Reg. No. 32,121; Gregory M. Doudnikoff, Reg. No. 32,847; Edward H. Duffield, Reg. No. 25,970; Jerry W. Herndon, Reg. No. 27,901; Gerald R. Woods, Reg. No. 24,144; Jeanine S. Ray-Yarletts, Reg. No. 39,808; Joseph C. Redmond, Jr., Reg. No. 18,753; John E. Hoel, Reg. No. 26,279; Christopher A. Hughes, Reg. No. 26,914; and Edward A. Pennington, Reg. No. 32,588;

AND also,

Send all correspondence to: Jeanine S. Ray-Yarletts, IBM Corporation T81/062; PO Box 12195; Research Triangle Park, NC 27709.

First Inventor: Richard A. Floyd

Signature:

Richard A. Floyd

30-Jun-00

Date

Residence: 112 Wolf's Trail, Chapel Hill, North Carolina ~~27514~~

27516

Citizenship: United States of America

Post Office Address: same as residence

Second Inventor: John R. Hind

Signature:

John R. Hind

6/30/00

Date

Residence: 5005 Barton's Enclave Lane, Raleigh, North Carolina 27613

Citizenship: United States of America

Post Office Address: same as residence

Third Inventor: Marcia L. Peters

Signature:

Marcia L. Peters

6/30/00

Date

Residence: 712 Lochgarton Lane, Raleigh, North Carolina 27614

Citizenship: United States of America

Post Office Address: same as residence

Fourth Inventor:

Brad B. Topol

Signature:

Brad B. Topol

6/30/00

Date

Residence: 209 Fern Ridge Drive, Raleigh, North Carolina 27606

Citizenship: United States of America

Post Office Address: same as residence